Serial No. 09/996,276

AMENDMENTS TO THE CLAIMS:

1 1.   (Previously Presented) A method for the automatic configuration of a

2 bi-directional Internet Protocol (IP) communication device, comprising:

3   broadcasting a request from a bi-directional Internet Protocol (IP)

4 communication device selected from either a DSL gateway or cable modem for basic

5 configuration details for the IP communication device, where said request contains a

6 unique bi-directional IP communication device identifier stored in the IP communication 7

device and associated with a unique user;

8   receiving said basic configuration details including an IP address from a

9 server, where said basic configuration details are assigned to said unique user based on 10

said unique bi-directional IP communication device identifier; and

11   configuring said bi-directional IP communication device with

12   said basic configuration details.

1 2.   (Previously Presented)The method of claim 1, wherein said broadcasting further

2 comprises broadcasting said request for basic configuration details, including said IP.

3 address, to a Dynamic Host Configuration Protocol (DHCP) server, where

4 said bi-directional IP communication device is a Digital Subscriber Line (DSL)

5 gateway.

1 3.   (Previously Presented)The method of claim 2, wherein said receiving comprises

2 obtaining said IP address from said DHCP server.

1 4.   (Original)The method of claim 1, further comprising transmitting a configuration

2 request for additional configuration details.

1 5.   (Original)The method of claim 4, further comprising receiving said additional

2 configuration details specific to said unique user.

2

Serial No. 09/996,276

1 6.   (Original)The method of claim 5, further comprising configuring said bi-

2 directional IP communication device with said additional configuration details.

1 7.   (Original)The method of claim 1, further comprising, before said broadcasting

2 step, the steps of:

3   connecting said bi-directional IP communication device to an analog

4 telephone line; and

5   powering said bi-directional IP communication device on.

1 8.   (Original)The method of claim 1, further comprising, before said broadcasting

2 step, the step of automatically detecting a DSL communication circuit.

1 9.   (Original)The method of claim 1, further comprising, before said broadcasting

2 step, the step of automatically determining Permanent Virtual Circuit (PVC)

3 details for communications between said bi-directional IP communication

4 device and a communications network.

1 10.   (Original)The method of claim 9, wherein said determining comprises the step of

2 ascertaining a VPINCI (Virtual Path Identifier/Virtual Channel Identifier) pair

3 for said communications.

1 11.   (Original)The method of claim 1, wherein said broadcasting comprises

2 broadcasting a DHCP Discover request.

1 12.   (Original)The method of claim 1, wherein said receiving comprises acquiring a

2 DHCP Offer message from a DHCP server.

3

Serial No. 09/996,276

1   13.   (Previously Presented) The method of claim 1, further comprising, prior to said

2   configuring step, the steps of:

3   sending a DHCP Request message to a DHCP server; and

4   receiving a DHCP acknowledge message from said DHCP

5   server.

1   14.   (Original)The method of claim 1, wherein said broadcasting and receiving steps

2   occur automatically without any communication between said bi-directional IP

3   communication device and a client computer coupled to said bi-directional IP

4   communication device.

1   15.   (Original)The method of claim 1, further comprising, prior to said configuring

2   step, the steps of:

3   assigning said unique bi-directional IP communication device

4   identifier to said bi-directional IP communication device; and

5   associating said unique bi-directional IP communication device

6   identifier with said unique user.

1   16.   (Currently Amended)The method of claim 15, further comprising generating a

2   configuration table listing bi-directional-IP communication device identifiers, ~~and~~

3   associated users and each user's basic configuration details.

4

Serial No. 09/996,276

1   17.   (Previously Presented)A bi-directional IP communication device, comprising:

2   a Central Processing Unit (CPU);

3   communication circuitry;

4   input/output ports; and

5   a memory containing:

6   a unique bi-directional IP communication device

7   identifier for a DSL gateway or cable modem;

8   instructions for broadcasting a request from the device for basic

9   configuration details for the IP communication device, where said request

10   contains a unique bi-directional IP communication device identifier

11   associated with a unique user;

12   instructions for receiving said basic configuration details including 13

an IP address from a server, where said basic configuration details is

14   assigned to said unique user based on said unique bi-directional IP

15   communication device identifier; and

16   instructions for configuring said bi-directional IP

17   communication device with said basic configuration details.

1   18.   (Previously Presented)The bi-directional IP communication device of claim 17,

2   wherein said instructions for broadcasting further comprise instructions for

3   broadcasting said request for basic configuration details, including said IP

4   address, to a Dynamic Host Configuration Protocol (DHCP) server, where

5   said bi-directional IP communication device is a Digital Subscriber Line (DSL)

6   gateway.

5

Serial No. 09/996,276

1   19.   (Previously Presented)A computer program product for use in conjunction with a

2   computer system for the automatic configuration of a bi-directional Internet Protocol (IP)

3   communication device, the computer program product comprising a computer

4   readable storage and a computer program stored therein, the computer

5   program comprising:

6   instructions for broadcasting a request from a bi-directional

7   Internet Protocol (IP) communication device selected from either a DSL

8   gateway or cable modem for basic configuration details for the IP

9   communication device, where said request contains a unique bi-directional 10

        IP communication device identifier stored in the IP communication device 11

     and associated with a unique user;

12   instructions for receiving said basic configuration details including 13

        an IP address from a server, where said basic configuration details is

14   assigned to said unique user based on said unique bi-directional IP

15   communication device identifier; and

16   instructions for configuring said bi-directional IP

17   communication device with said basic configuration details.

1   20.   (Previously Presented)The computer program product of claim 19, wherein said

2   instructions for broadcasting further comprise instructions for broadcasting said request

3   for basic configuration details, including said IP address, to a Dynamic Host

4   Configuration Protocol (DHCP) server, where said bi-directional IP

5   communication device is a Digital Subscriber Line (DSL) gateway.

1   21.   (Currently Amended) The method of claim ~~11~~1, wherein a configuration table

2   listing device identifiers, their associated users, and each user's basic configuration

3   details is stored in the server.

6

Serial No. 09/996,276

1. 22.   (Currently Amended) A method for the automatic configuration of a

2 bi-directional Internet Protocol (IP) communication device, comprising:

3   connecting a bi-directional Internet Protocol (IP) communication device

4   selected from either a DSL gateway or cable modem to a network, said device

5   having a unique device identifier stored therein that is associated at a server with a 6

   unique user prior to connection, said server storing a configuration table listing

7   device identifiers, their associated users and each user's basic configuration

8   details;

9   broadcasting a request from the IP communication device for basic

10   configuration details for the IP communication device over the network to the

11   server, where said request contains the unique device identifier;

12   receiving said basic configuration details including an IP address from the 13

   server, where said basic configuration details for the IP communication device are 14

   assigned to said unique user based on said unique device identifier; and

15   configuring said IP communication device with said basic configuration

16   details.

1 23.   Cancelled

1 24.   Cancelled

1 25.   (Previously Presented)The method of claim 22, further comprising, before said

2 broadcasting step, the step of automatically detecting a dial-tone for the internet protocol.

7

Serial No. 09/996,276

1   26.   (Previously Presented) A method for the automatic configuration of a

2   bi-directional Internet Protocol (IP) communication device, comprising:

3   providing a bi-directional Internet Protocol (IP) communication device selected

4   from either a DSL gateway or cable modem having a unique device identifier stored

5   therein;

6   associating the device identifier with a user identifier for a unique user of the IP

7   communication device;

8   providing the IP communication device to the unique user;

9   providing the device identifier and the user identifier to an internet service

10 provider (ISP);

12   generating a configuration table listing device identifiers, their associated users, 12

    and each user's basic configuration details including an IP address;

13   storing the configuration table in a server;

14   connecting the IP communication device to a network at a user site;

15   broadcasting a request from the IP communications device for basic configuration

16 details for the IP communication device to the server over the network, where said

17 request contains the unique device identifier;

18   identifying the user's basic configuration details in the configuration table from

19 the device identifier;

20   transmitting the basic configuration details to the user site IP communications

21 device;

22   receiving said basic configuration details from the server; and

23   configuring said IP communication device with said basic configuration details.

1   27.   (Previously Presented)The method of claim 26, further comprising, before said

2   broadcasting step, the step of automatically detecting a dial-tone for the internet protocol.

8